

## Model 1095A/C Industrial GPS Clock



Model 1095C

The Arbiter Systems®, Inc. Model 1095A/C Industrial GPS Clock is a GPS timing source for industrial applications that require common timing signals, such as IRIG-B, 1PPS, and RS-232 serial timecodes, in a small, rugged enclosure suitable for indoor and outdoor applications. The Model 1095A/C with 250 ns (typical < 100 ns) worst-case accuracy meets the most demanding requirements including synchrophasors. The Model 1095C has a see-through cover with 4 LEDs to monitor operating status and a large 7-segment LED time display. The Model 1095A has an opaque cover. The 1095A/C comes standard with a built-in GPS antenna or can be configured with an optional external antenna.

Four outputs, with terminal strip connectors, provide three high-drive 5 Vdc (250 mA at > 4 V) outputs: IRIG-B00x level-shift, programmable pulse A and programmable pulse B, and one 4.5 Vpp modulated IRIG-B (IRIG-B12x) signals. All of the outputs have

substantial drive capability to easily drive multiple loads in parallel. Two serial (RS-232) ports can be used for setup, or for serial timecodes such as IRIG-J. An RS-485 port (transmit only) is also included.

Standard features include a GPS Data Backup Battery, one Form C fail-safe relay, and Event Capture capability. The GPS Data Backup Battery maintains the real-time clock, almanac and ephemeris data in the 12-channel GPS receiver to speed acquisition. Satellites are acquired in as little as 15 seconds after a brief power loss. One Form C (SPDT) fail-safe relay is selectable to Fault, Unlocked, or Programmable Pulse functions and is compatible with digital fault recorder inputs. The Event Capture records events triggered from the dedicated, optically-isolated input or from either serial port receive line with 100 ns resolution.

The Model 1095A/C accepts nominal 12/24 Vdc (9-30 Vdc) power from battery or other power sources.

*Specifications subject to change without notice.*

## Model 1095A/C Specifications

### Receiver Characteristics

#### Timing Accuracy

Specifications apply at the 1 PPS, IRIG-B Level-Shift and Programmable Pulse outputs, with US Department of Defense Selective Availability (SA) as of date of publication.

UTC/USNO  $\pm 250$  ns peak;  $< \pm 100$  ns typical (SA off)

#### Position Accuracy

10 meters, rms, 90% confidence

#### Satellite Tracking

12 channel, C/A code (1575.42 MHz). Receiver simultaneously tracks up to twelve satellites.

#### Acquisition

150 seconds typical, cold start

15 minutes, 90% confidence, cold start

40 seconds, typical, with almanac  $< 1$  month old

15 seconds, typical, with ephemeris  $< 4$  hours old

### I/O Configuration

#### Outputs

Four Total: three high-drive 5 Vdc (250 mA at  $> 4$  V), one analog (4.5 Vpp), terminal strip connectors.

Output 1: Programmable Pulse A

Output 2: IRIG-B00x level-shift

Output 3: Programmable Pulse B

Output 4: Modulated IRIG-B

#### Event Input

One opto-isolated event capture input with 100 ns resolution, terminal strip inputs for 5 to 12, 24 to 48, and 120 to 240 Vdc nominal input.

#### Relay Contact

One, Form C (SPDT) fail-safe, 0.3 A at 130 Vdc; jumper selectable to Fault, Out-of-Lock, Programmable Pulse A (PPA), Programmable Pulse B (PPB), Stabilized, and Event-In functions.

Fail-safe means the relay indicates 'fault' or 'unlocked' condition with power off.

### I/O Configuration (cont.)

#### Programmable Pulse Output

Two programmable pulse outputs (5 Vdc), PPA and PPB.

Modes:

- 1 PPS
- Every 1 to 60,000 seconds, starts top of the minute
- Hourly at a specified offset
- Daily at a specified time of day
- One shot at a specified time of year
- 1 to 1000 PPS squarewave (PPB only)
- Aux IRIG Mode (PPB only)

Pulse duration is programmable from 0.01 to 600 seconds, except in one-shot mode, where the output is Low prior to the specified time and High thereafter.

Aux IRIG Mode provides an additional unmodulated IRIG-B signal on the PPB output

### Interface

#### Operator

1095C Display 6-digit LED Time of Day (20 mm)

Status LEDs Operate (green)  
Stabilized (green)  
Unlocked (red)  
Fault (red)

Setup (via remote interface) Local time offset  
IRIG Setup: Local/UTC/IEEE 1344  
Daylight Saving Time:  
On/Off/Auto (Configurable)  
LED Brightness control  
Event input: Event/1 PPS Deviation  
Programmable Pulse Setup  
Antenna Cable Delay  
Out-of-Lock Time: 1 to 99 minute(s),  
Off, or Zero Delay  
Auto-Survey  
Relay Control  
RS-485 Output  
Serial port 2 (RS-232)  
Serial port 1 (RS-232): DIP Switches

## Model 1095A/C Specifications

### Interface (cont)

#### System

RS-232	1200 to 115200 baud; 7 or 8 data bits; 1 or 2 stop bits; even/odd/no parity (TXD, RXD, COM) Broadcast modes include: ASCII, Extended ASCII, ASCII with Time Quality, and Vorne (output once every second), Status (output on change of Status) and Custom Configurable Serial Time Code
RS-422/485	Transmit only, to drive multiple devices. Available Signals include: Serial Port 1, Serial Port 2, IRIG-B, PPA, PPB, and 1PPS.

### Power Requirements

#### Standard

Voltage	9 to 30 Vdc, 3 W max.; negative common 3.81 mm pluggable terminal strip
---------	---

### General

#### Physical

Size	180 x 120 x 60 mm (7.1 x 4.7 x 2.4 in.) plus cable gland
Weight	1 kg (2.2 lbs), net 2 kg (4.4 lbs), shipping
Mounting	4 mounting feet included
Antenna	Built-in or optional external
Sealing Cable Port	Accepts up to a 16 conductor cable with an OD from 6 to 12 mm (0.24 to 0.47 in.)
Degree of Protection	IP65 (IEC 60529) NEMA 1, 2, 4, 4x, 12, 13

#### Environmental

Temperature	Operating: -40° to +85° C
EMC	Radiated susceptibility: passes walkie-talkie test

### Certifications and Approvals

CE mark/label and certificate

### Options

<u>Option Description</u>	<u>Order No.</u>
External Antenna	1095Aopt01 1095Copt01

Internal antenna is removed when the external antenna option is ordered.

### Accessories

#### Included

<u>Description</u>	<u>Order No.</u>
Operation Manual	PD0039700
Sealing Cable Port: Accepts cable OD from 6 to 12 mm (0.24 to 0.47 in.)	HP0022601

#### Available

<u>Description</u>	<u>Order No.</u>
Programming Port Cable <sup>2</sup>	AS0067200
DIN Rail Mounting Assembly	AS0093700
GPS Antenna, pipe mountable <sup>1,3</sup>	AS0087800
GPS Antenna Mounting Kit <sup>1</sup>	AS0044600
2 m (6 ft) RG-6 Antenna Cable <sup>1</sup>	CA0021302
6 m (20 ft) RG-6 Antenna Cable <sup>1,3</sup>	CA0021306
15 m (50 ft) RG-6 Antenna Cable <sup>1</sup>	CA0021315
30 m (100 ft) RG-6 Antenna Cable <sup>1</sup>	CA0021330
Antenna Grounding Block Kit <sup>1,3</sup>	AS0048900
GPS Surge Protector <sup>1</sup>	AS0094500
Sealing Cable Port: Accepts cable OD from 5 to 9 mm (0.20 to 0.35 in.)	HP0022602

<sup>1</sup> For use with external antenna. Longer cable lengths are available.

<sup>2</sup> Modular DB9 to RJ11 Adapter and RJ11 Cable 7 ft.

<sup>3</sup> Included with 1095Aopt01 and 1095Copt01